# Led Lamp Candle

**5w** POWER **40w** LIGHT

WARM WHITE 3000K | NATURAL WHITE 4000K | COLD WHITE 6500K

SAVE 85% ENERGY | ISTANT LIGHT | E14 | A+

MERCURY Hg FREE | 30.000 HOURS LIFE | BEAMING ANGLE 270° | 3 YEARS WARRANTY

| | FLED17207 | FLED17206 | FLED17237 |
|---|---|---|---|
| Color temperature | Warm White 3.000K | Natural White 4.000K | Cold White 6.500K |
| Power consumption | 5W | 5W | 5W |
| Equivalent Power | 40W | 40W | 40W |
| Lumens | 470LM | 470LM | 470LM |
| Efficiency | 94 LM/W | 94 LM/W | 94 LM/W |
| Energy Power | A+, 5 kWh/1000h | A+, 5 kWh/1000h | A+, 5 kWh/1000h |
| CRI (Ra) | >80 | >80 | >80 |
| Beam Angle | 270° | 270° | 270° |
| Screw Base | E14 | E14 | E14 |
| Commercial Type | Candle | Candle | Candle |
| Body type | Plastic | Plastic | Plastic |
| Input Voltage Range | 170-240Vac 50/60Hz | 170-240Vac 50/60Hz | 170-240Vac 50/60Hz |
| Power factor | 0,5 | 0,5 | 0,5 |
| Start Time 60% | Instant full light | Instant full light | Instant full light |
| Life Spam | 30.000 hours | 30.000 hours | 30.000 hours |
| On/Off | 50.000 | 50.000 | 50.000 |
| Dimmable | No | No | No |

Italian DESIGN | REFURBISHED COMPONENTS | RoHS COMPLIANT | CE

© 2015 Tecnoware Power Systems. The technical data can be varied without prior notice.

Dimensions




Luminous Intensity Distribution Diagram





TECNOWARE

www.tecnoware.com